



(12) **United States Patent**
King et al.

(10) **Patent No.:** **US 9,002,723 B2**
(45) **Date of Patent:** **Apr. 7, 2015**

(54) **METHOD AND APPARATUS FOR
AUTOMATIC LOCATION-SPECIFIC
CONFIGURATION MANAGEMENT OF A
REMOVABLE METER UNIT**

(75) Inventors: **David William King**, Rancho Santa Fe,
CA (US); **Alexander Schwarz**, San
Diego, CA (US); **Stephen John Hunter**,
San Diego, CA (US)

(73) Assignee: **IPS Group, Inc.**, San Diego, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1015 days.

(21) Appl. No.: **12/355,740**

(22) Filed: **Jan. 16, 2009**

(65) **Prior Publication Data**

US 2009/0183966 A1 Jul. 23, 2009

Related U.S. Application Data

(60) Provisional application No. 61/022,208, filed on Jan.
18, 2008, provisional application No. 61/022,213,
filed on Jan. 18, 2008.

(51) **Int. Cl.**

G07B 15/00 (2011.01)
G07B 15/02 (2011.01)
G06Q 50/30 (2012.01)
G07F 17/24 (2006.01)
G06Q 10/00 (2012.01)
G06F 17/00 (2006.01)
G06G 7/00 (2006.01)

(52) **U.S. Cl.**

CPC **G07B 15/02** (2013.01); **G06Q 50/30**
(2013.01); **G07F 17/24** (2013.01)

(58) **Field of Classification Search**

USPC 340/932.2; 705/1.1, 13, 400
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,161,046 A 6/1939 Hitzeman
2,822,682 A 2/1958 Sollenberger

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2377010 12/2001
EP 0980055 B1 2/2000

(Continued)

OTHER PUBLICATIONS

International Search Report dated Apr. 26, 2011 in PCT Application
No. PCT/US2010/047907, 3 pages.

(Continued)


Primary Examiner — George Chen

(74) *Attorney, Agent, or Firm* — Wilson Sonsini Goodrich &
Rosati

(57) **ABSTRACT**

A meter apparatus and method of operating a removable
meter apparatus are described. The meter apparatus includes
a tag associated with unique tag identification information
and configured to be permanently affixed to a location hous-
ing at a unique physical location, and includes a removable
meter unit configured to mate with the location housing and
receive the tag identification from the tag and report the tag
identification to a data manager configured to associate an
identifier of the removable meter unit with the tag identifica-
tion and unique physical location, and associate configuration
information for the physical location with the removable
meter unit and the tag identification. The unique physical
location can comprise a single-space parking location.

14 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2,832,506 A 4/1958 Hatcher
 2,988,191 A 6/1961 Grant
 3,721,463 A 3/1973 Attwood et al.
 4,812,805 A 3/1989 Lachat et al.
 4,823,928 A 4/1989 Speas
 4,825,425 A 4/1989 Turner
 4,875,598 A 10/1989 Dahl
 4,880,097 A 11/1989 Speas
 4,895,238 A 1/1990 Speas
 5,065,156 A 11/1991 Bernier
 5,222,076 A 6/1993 Ng et al.
 5,244,070 A 9/1993 Carmen et al.
 5,273,151 A 12/1993 Carmen et al.
 5,360,095 A 11/1994 Speas
 5,442,348 A * 8/1995 Mushell 340/932.2
 5,563,491 A 10/1996 Tseng
 5,614,892 A 3/1997 Ward, II et al.
 5,617,942 A 4/1997 Ward, II et al.
 5,648,906 A 7/1997 Amirpanahi
 5,659,306 A 8/1997 Bahar
 5,737,710 A 4/1998 Anthonyson
 5,778,067 A 7/1998 Jones et al.
 5,806,651 A 9/1998 Carmen et al.
 5,833,042 A 11/1998 Baitch et al.
 5,841,369 A 11/1998 Sutton et al.
 5,852,411 A 12/1998 Jacobs et al.
 5,954,182 A 9/1999 Wei
 6,037,880 A 3/2000 Manion
 6,111,522 A 8/2000 Hiltz et al.
 6,116,403 A 9/2000 Kiehl
 6,195,015 B1 2/2001 Jacobs et al.
 6,229,455 B1 5/2001 Yost et al.
 6,230,868 B1 5/2001 Tuxen et al.
 6,309,098 B1 10/2001 Wong
 6,312,152 B2 11/2001 Dee et al.
 6,456,491 B1 9/2002 Flannery et al.
 6,457,586 B2 10/2002 Yasuda et al.
 6,505,774 B1 1/2003 Fulcher et al.
 6,747,575 B2 * 6/2004 Chauvin et al. 340/932.2
 6,856,922 B1 2/2005 Austin et al.
 6,914,411 B2 7/2005 Couch et al.
 6,929,179 B2 8/2005 Fulcher et al.
 7,019,420 B2 3/2006 Kogan et al.
 7,027,773 B1 4/2006 McMillin
 7,183,999 B2 * 2/2007 Matthews et al. 345/1.1
 7,222,031 B2 5/2007 Heatley
 7,237,716 B2 7/2007 Silberberg
 7,388,349 B2 6/2008 Elder et al.
 7,748,620 B2 7/2010 Gomez et al.
 7,772,720 B2 8/2010 McGee et al.
 7,806,248 B2 10/2010 Hunter et al.
 7,854,310 B2 12/2010 King et al.
 7,855,661 B2 12/2010 Ponert
 7,933,841 B2 4/2011 Schmeier et al.
 8,479,909 B2 7/2013 King et al.
 8,513,832 B2 8/2013 Hunter et al.
 8,566,159 B2 10/2013 King et al.
 8,590,687 B2 11/2013 King et al.
 8,595,054 B2 11/2013 King et al.
 2001/00112241 A1 8/2001 Dee et al.
 2001/0047278 A1 * 11/2001 Brookner et al. 705/1
 2001/0051531 A1 12/2001 Singhal et al.
 2002/0008639 A1 1/2002 Dee
 2003/0092387 A1 5/2003 Hjelmvik
 2003/0112151 A1 6/2003 Chauvin et al.
 2003/0112597 A1 6/2003 Smith
 2003/0121754 A1 7/2003 King
 2003/0128010 A1 7/2003 Hsu
 2003/0128136 A1 7/2003 Spier et al.
 2003/0140531 A1 7/2003 Pippins
 2003/0144972 A1 * 7/2003 Cordery et al. 705/401
 2003/0169183 A1 9/2003 Korepanov et al.
 2003/0179107 A1 9/2003 Kibria et al.
 2004/0068434 A1 * 4/2004 Kanekon 705/13
 2004/0084278 A1 5/2004 Harris et al.

2004/0094619 A1 5/2004 Silberg
 2004/0181496 A1 9/2004 Odinotski et al.
 2004/0264302 A1 * 12/2004 Ward, II 368/90
 2005/0040951 A1 2/2005 Zaleski et al.
 2005/0178639 A1 8/2005 Brumfield et al.
 2005/0192911 A1 * 9/2005 Mattern 705/401
 2006/0021848 A1 2/2006 Smith
 2006/0116972 A1 6/2006 Wong
 2006/0149684 A1 7/2006 Matsuura et al.
 2006/0152349 A1 7/2006 Ratnakar
 2006/0267799 A1 11/2006 Mendelson
 2007/0016539 A1 1/2007 Groft et al.
 2007/0094153 A1 * 4/2007 Ferraro 705/67
 2007/0114849 A1 5/2007 Falik et al.
 2007/0119682 A1 5/2007 Banks et al.
 2007/0136128 A1 6/2007 Janacek et al.
 2007/0184852 A1 8/2007 Johnson et al.
 2007/0210935 A1 9/2007 Yost et al.
 2008/0071611 A1 3/2008 Lovett
 2008/0093454 A1 * 4/2008 Yamazaki et al. 235/454
 2008/0147268 A1 6/2008 Fuller
 2008/0208680 A1 8/2008 Cho
 2008/0238715 A1 10/2008 Cheng et al.
 2008/0245638 A1 10/2008 King et al.
 2009/0026842 A1 1/2009 Hunter et al.
 2009/0032368 A1 2/2009 Hunter et al.
 2009/0095593 A1 4/2009 King et al.
 2009/0109062 A1 4/2009 An
 2009/0159674 A1 6/2009 King et al.
 2009/0192950 A1 7/2009 King et al.
 2009/0267732 A1 10/2009 Chauvin et al.
 2009/0284907 A1 11/2009 Regimbal et al.
 2009/0315720 A1 12/2009 Clement et al.
 2010/0188932 A1 7/2010 Hanks et al.
 2011/0057815 A1 3/2011 King et al.
 2011/0060653 A1 3/2011 King et al.
 2011/0203901 A1 8/2011 King et al.
 2013/0005445 A1 1/2013 Walker et al.
 2013/0027218 A1 1/2013 Schwarz et al.
 2013/0238406 A1 9/2013 King et al.
 2013/0285455 A1 10/2013 Hunter et al.
 2014/0040028 A1 2/2014 King et al.
 2014/0172518 A1 6/2014 King et al.
 2014/0174881 A1 6/2014 King et al.
 2014/0231505 A1 8/2014 King et al.
 2014/0289025 A1 9/2014 King et al.

FOREIGN PATENT DOCUMENTS

FR 2837583 9/2003
 JP 2002-099640 A 4/2002
 JP 2005-267430 A 9/2005
 KR 10-2005-0038077 A 4/2005
 WO WO-2005-031494 4/2005
 WO WO-2006-095352 9/2006
 WO WO-2009-154787 12/2009

OTHER PUBLICATIONS

International Search Report dated Mar. 30, 2011 in PCT Application No. PCT/US2010/047906, 3 pages.
 Meter Solutions, Single-Space Meters brochure, downloaded from www.duncansolutions.com website, revised Apr. 2006, 2 pages.
 (Cell Net Data Systems) "First Wireless Monitoring of Parking Meters Results in Theft Arrests Using CellNet Data Systems Technology," PRNewswire, May 11, 1999, 2 pages.
 International Search Report dated Oct. 27, 2008 in PCT application No. PCT/IB06/054574, 2 pages.
 International Preliminary Report on Patentability dated Mar. 15, 2012 for International Application No. PCT/US2010/047907, 6 pages.
 International Preliminary Report on Patentability dated Mar. 6, 2012 for International Application No. PCT/US2010/047906, 5 pages.
 International Preliminary Report on Patentability dated Mar. 10, 2009 in PCT application No. PCT/IB06/054574, 5 pages.
 U.S. Appl. No. 13/786,387, filed Mar. 5, 2013, David William King, Flatley, "In San Francisco, Hackers Park for Free," Read filed under

(56)

References Cited

OTHER PUBLICATIONS

Misc. Gadgets, downloaded from www.engadget.com website on May 3, 2010, originally posted on Jul. 31, 2009, 5 pages.

Howland, S., "How M2M Maximizes Denver's Revenue," Field TechnologiesOnline.com, Oct. 2011, pp. 9-12 [online] [retrieved Mar. 5, 2013], Retrieved from <http://www.fieldtechnologiesonline.com/doc.mvc/How-M2M-Maximizes-Denvers-Revenue-0001>.

PCT/US2012/048190 International Search Report dated Jan. 22, 2013.

The U.S. Conference of Mayors Presents 'Best Practice' Awards, Los Angeles, New Orleans, Elizabeth, N.J. and Long Beach, CA Honored

for Excellence & Innovation in Public-Private partnerships, Press Release Jan. 20, 2012.

U.S. Appl. No. 14/059,260, filed Oct. 21, 2013, King et al.



U.S. Appl. No. 14/185,691, filed Feb. 20, 2014, King et al.

U.S. Appl. No. 14/260,234, filed Apr. 23, 2014, King et al.

Fidelman. Time's Running Out for Parking Meters at Present Locations: \$270,000 Cited as Replacement Cost. City Employees Who Ticket Motorists Find Electronic Meters Unsuitable. The Gazette, Final Edition, Montreal, Quebec, Canada, Nov. 12, 2002, p. A7.

U.S. Appl. No. 14/558,564, filed Dec. 2, 2014, King et al.

* cited by examiner






FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5




FIG. 6

**METHOD AND APPARATUS FOR
AUTOMATIC LOCATION-SPECIFIC
CONFIGURATION MANAGEMENT OF A
REMOVABLE METER UNIT**

CROSS-REFERENCES TO RELATED
APPLICATIONS

This application claims the benefit of U.S. Provisional Patent Application No. 61/022,208 filed Jan. 18, 2008 entitled "A PARKING METER" and claims the benefit of U.S. Provisional Application No. 61/022,213 filed Jan. 18, 2008 entitled "THE OPERATION OF PARKING METERS", both of which are incorporated herein by reference in their entirety for all purposes. This application is related to U.S. Non-provisional application filed on even date herewith entitled "METHOD AND APPARATUS FOR OPERATING A REMOVABLE METER UNIT", which is incorporated herein by reference.

BACKGROUND

1. Field of the Invention

The invention relates generally to electronic communications for reporting, and more particularly, but not by way of limitation, to location-specific transaction reporting for vehicle parking.

2. Description of the Related Art

A "meter" can be any of various devices configured to measure time, distance, speed, or intensity, or to indicate, record, and/or regulate an amount or volume, such as, for example, the flow of a gas or an electric current. As technology has advanced, meters have also become more advanced. Meters that measure the passage of time, e.g., parking meters, typically include timer mechanisms similar to those of mechanical watches. Since these timer mechanisms had limited life spans, the parking meters were constructed with a fixed housing that was configured to receive a replaceable meter unit including the meter timer mechanism. When the timer mechanism wore out, the meter unit could be replaced. Other types of meters that can have replaceable meter units include water meters and gas meters that measure the flow of material, such as water or gas, respectively.

Many mechanical meters have been replaced by digital-based meters. Digital meter units can have longer life spans than their mechanical predecessors, but they still are replaced when they malfunction, are damaged, or even when the technology changes.

With advances in communications, e.g., wireless telecommunications, it is possible to monitor many meters remotely. For example, a group of meters can report information to a central data manager using wireless communications. The information reported can be related to financial transactions such as credit card information or periodic measures such as the amount of gas or water consumed. Meters that communicate local information are often associated with a specific geographic location. For example, a meter might be associated with locations such as a parking spot, a house, a ticket booth, a cash register, a vending machine, and so forth. The central data manager can maintain a database that associates each meter with corresponding meter information such as transactions or consumption measures.

The central data manager that receives reporting information from a local meter needs to know what meter is associated with the received reporting information. The reporting information can be associated with the proper meter by determining an identifier of the meter, such as a meter unit serial

number or ID. When a meter unit is replaced, the central data manager needs to update its reporting information for the old meter with the unit ID of the new meter unit. Replacement of meter units is a relatively regular occurrence, as meter units fail or require periodic maintenance or become damaged.

Updating of meter information in the database upon meter unit replacement has typically been performed manually by entering the new meter unit ID into the database of the central data manager and manually associating the new meter unit ID with the reporting information and disassociating the old meter unit ID with the reporting information. In addition, during operation a meter unit may need to be configured with various operational parameters that determine rates and parking rules for the meter location. This operational configuring has also typically been performed manually, often on the meter unit itself. Manual data entry and configuring of the meter reduces efficiency by increasing the time to update and reduces reliability by potentially increasing the number of errors in the central data manager database and in the configuration information of the meter.

From the discussion above, it should be apparent that there is a need for more efficient and reliable updating of location-specific meter information to a data manager. The present invention satisfies this need.

SUMMARY

A meter apparatus includes a tag associated with unique tag identification information and configured to be permanently affixed to a location housing at a physical location, and a removable meter unit configured to mate to the location housing and receive the tag identification from the tag and report the tag identification to a data manager that is configured to associate an identifier of the removable meter unit with the reported tag identification and unique physical location and to associate configuration information for the physical location with the removable meter unit and the reported tag identification. In this way, meter information at a specific location can be automatically updated and reported to a data manager with increased efficiency and reliability.

The meter apparatus can include a memory module to store information regarding a transaction history. The tag is configured to provide its unique identification information to the removable meter unit, and thereby provide its unique physical location as well. The memory module can be configured to store information indicative of a transaction history for the meter apparatus, including a payment collection history. The memory module can be incorporated with the tag. A removable meter unit that is mated with the housing can receive the identification information from the tag. With the tag identification information, the meter unit can determine its physical location and configuration information, including operating parameters and transaction history for the physical location. Such parameters and information can be determined by the meter unit directly from the tag or from a data manager upon providing the tag identification information.

Another meter apparatus includes a removable meter unit that receives a tag identification associated with a unique physical location and reports the tag identification to a data manager such that the data manager associates an identifier of the removable meter unit with the physical location and the tag identification, and associates operating parameters for the physical location with the removable meter unit and the tag identification. The tag identification is received from a tag associated with the physical location, where the tag is perma-

nently attached to a location housing that is fixedly placed at the physical location and that is configured to mate with the removable meter unit.

A method of operating a meter includes receiving a tag identification associated with a unique physical location at which a removable meter unit is placed, determining configuration information associated with the tag identification and the physical location, and associating the determined configuration information with the removable meter unit. The tag identification is received from a tag associated with the physical location, and wherein the tag is permanently attached to a location housing that is fixedly placed at the physical location and the location housing is configured to mate with the removable meter unit.

In other aspects, the tag is configured to receive information indicative of removal of a cash collection box containing currency received at the removable meter unit. Upon receiving the information indicative of the removal of the cash collection box, the tag can be configured to initiate storing transaction information in the memory module. The transaction information can include data indicating the amount of currency collected at the removable meter unit based on the stored payment collection history. In addition, the tag can be further configured to reset the transaction history stored in the memory module in response to receiving the information indicative of the removal of the cash collection box.

In yet another embodiment, a parking meter includes a meter unit; a cash collection box; and a tag device for monitoring the content of the cash collection box. The tag device may have a unique tag identifier, which is associated with the parking meter. The tag identifier may be associated with a unique location of the parking meter, such that the cash collected at each unique location may be monitored during use, irrespective of the particular meter unit or cash collection box used, from time-to-time at each unique location.

The tag device may have a memory module in which the value of coins in the cash collection box of the parking meter in question is recorded during use. The memory module may be of the non-volatile type and the value may be externally readable. The value may also be reset externally. Conveniently the memory module may record a total value collected and an interim value.

In another aspect, the parking meter may have a housing, with the tag device being secured thereto or therein. The meter unit may communicate with the tag device, to receive tag device information and to record therein the number and/or value of coins received by the meter unit. This may be effected by means of a wired, radio, or optical link between the meter unit and tag device. The tag device may comprise a small microprocessor with nonvolatile flash memory, such as a wired memory device, or can comprise an RFID tag or the like.

As described further herein, cash collected at each meter location may be monitored and recorded, otherwise than by the meter unit, such that a defective meter unit may be removed and replaced with another, without replacing the cash collection box and without affecting monitoring of the cash collected at that location.

Further areas of applicability of the present disclosure will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating various embodiments, are intended for purposes of illustration only and are not intended to necessarily limit the scope of the disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention is described, by way of non-limiting examples, with reference to the accompanying drawings, in which:

FIGS. 1A and 1B illustrate embodiments of single-space parking meters constructed in accordance with the invention.

FIGS. 2A and 2B show schematically a removable meter unit and an auxiliary device as used in the parking meter of FIGS. 1A and 1B.

FIG. 3 shows schematically an embodiment of a parking meter system that monitors a number of the parking meters such as those of FIG. 1A and/or FIG. 1B.

FIG. 4 shows schematically an example of a local group of parking meters that can be monitored by the parking meter system of FIG. 3.

FIG. 5 shows schematically another example of a local group of parking meters that can be monitored by the parking meter system of FIG. 3.

FIG. 6 shows a flowchart of a process for operating parking meters such as the parking meters of FIGS. 1A and/or 1B in the system of FIG. 3.

In the appended figures, similar components and/or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label (e.g. "18") by a dash and a second label that distinguishes among the similar components (e.g. "18-1" and "18-2"). If only the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

DETAILED DESCRIPTION

In one embodiment of a meter apparatus as described herein, the meter apparatus includes a housing that is fixedly placed at a unique physical location and is configured to permanently receive a tag. The tag is associated with the unique physical location. The location housing is configured to mate with a removable meter unit. The meter apparatus includes a memory module to store information regarding a transaction history for the physical location. The tag is configured to provide its unique identification information to the removable meter unit, and thereby provide the meter unit with its unique physical location as well. The memory module can be configured to store information indicative of a transaction history for the meter apparatus. A meter unit that is mated with the housing can receive the identification information from the tag. With the tag identification information, the meter unit can determine its physical location and configuration information, including operating parameters and transaction history for the physical location. During operation, the meter unit can continue to receive updated operating parameters and, if desired, can report its configuration information such as operational status in accordance with its tag identification information.

In another embodiment, the meter apparatus comprises a parking meter associated with a unique parking location, and a method of operating a parking meter includes transmitting radio signals to, and receiving radio signals from, a data manager.

The parking meter may be a single-space parking meter, comprising a parking meter that is associated with a single parking space that accommodates one vehicle.

A transceiver of the parking meter may be constructed from conventional equipment, which typically has a maximum range of up to 150 meters, but should preferably be capable of operation at less than 80 meters. The transceiver may communicate with a data manager that maintains a database with parking meter information stored according to the tag identification information.

It will thus be appreciated that one construction of a parking system may comprise a predetermined number of single-space parking meters that, together with an associated local data manager, form a local group, and the local data manager can communicate with a central data manager.

Yet another embodiment provides a vehicle parking control system that includes a number of parking meters in accordance with the invention that are grouped together; an associated local data manager which has a complementary transceiver for receiving radio transmissions from the grouped parking meters and a transmitter for transmitting signals to the grouped parking meters and a communication facility for communicating with a central data manager, the grouped parking meters and the associated local hub manager forming a local group.

The system may thus include a number of local groups and a central data manager.

It will be appreciated that the local data manager will typically be located no more than about 150 meters and preferably not more than about 80 meters from any of its associated group of parking meters.

The transceivers may operate in the 2.4 GHz frequency band and may have a power of between 1.0 mW and 6.0 mW.

The communication facility of the local data manager may communicate with the central data manager by means of a data channel, which may use a variety of networks, such as a cellular telephone network, a wireless LAN, a wired LAN, a mesh network or the Internet.

Communications between the parking meters and the central data manager may be in regard to payment authorization, status reports, fault reporting and/or configuration and software updates.

It will be appreciated by those skilled in the art that the local data managers may concentrate data received from their parking meters before communicating with the central data manager; synchronized time division multiplexing may be used to keep active transmit and receive times short; data may be encrypted; and messages may be acknowledged to improve reliable delivery.

Each group of parking meters and its associated local data manager may be in the form of a mesh radio network, such that certain parking meters may act as relays for other parking meters that don't have direct communication with the local data manager

Referring to FIG. 1A, an embodiment of a meter apparatus for a single parking space is designated generally by reference numeral 10-1. That is, the meter apparatus 10-1 comprises a single-space parking meter. The parking meter 10-1 includes a location housing 12, a cash collection box 14, a meter unit 16, and an auxiliary device 18-1 in the form of a tag. The location housing 12 is fixedly attached to a pole 20 that is in relatively close proximity to the parking space (not illustrated in FIG. 1A), so that the meter 10-1 is readily associated and identified with the parking space. The cash collection box 14, the meter unit 16, and the tag 18-1 are received in the location housing 12.

The tag 18-1 is attached to an inner surface of the housing 12, whereas the cash collection box 14 and meter unit 16 are removable and replaceable. In the example shown in FIG. 1A, the tag 18-1 is connectable to the meter unit 16 by means of a length of wire 22 and a plug-in connector 24, and can be powered by the meter unit 16 (e.g., by a battery, solar cell, or other power source associated with the meter unit 16). The tag device 18-1 may comprise a small microprocessor with non-volatile flash memory, such as the 1-wire memory device product called "DS2433" of Dallas Semiconductor from Maxim Integrated Products, Inc. of Sunnyvale, Calif., USA.

Referring to FIG. 1B, another embodiment of a single-space parking meter is designated generally by reference numeral 10-2. The parking meter 10-2 is similar to the parking meter 10-1 of FIG. 1A except that the FIG. 1B parking meter 10-2 includes a wireless tag 18-2 and the meter unit 16-2 includes a wireless transceiver 25. The wireless tag and the meter unit are capable of communication with each other over a wireless communication channel. The wireless tag 18-2 can be, for example, an RFID tag, a smart card that is powered by the wireless transceiver 25, or an ID token, or the like. The wireless transceiver 25 receives information from the tag 18-2 and, for example, can be a radio transceiver that uses WiFi, Bluetooth, WiMax, or other short-range wireless radio technology, in accordance with the wireless communication channel used by the tag.

In some embodiments, such as, for example, where the tag 18-2 is an RFID and/or a smart card, the wireless tag 18-2 is powered by the signal transmitted by the transceiver 25. In other embodiments, the wireless tag 18-2 can be powered by a battery. Because the distance from the wireless transceiver 25 to the tag 18-2 is relatively small, the power consumed by the wireless transceiver 25 and/or the tag 18-2 can be very low, such that a relatively small capacity battery that is compact provides sufficient power.

The wireless transceiver 25 of the parking meter 10-2 could be an Infrared (IR) transceiver. In that case, the transceiver 25 is aligned with the tag 18-2 such that the infrared beam of the transceiver is properly targeted at the tag 18-2.

In one embodiment, the wired tag 18-1 or the wireless tag 18-2 is used to monitor the content of the cash collection box 14, as will be explained below. Also as explained below, each tag 18 has a unique identifier that identifies the parking meter 10 with which it is used and which is associated with a unique physical location where the parking meter is fixedly located, e.g., the location of the pole 20 and the location housing 12.

In many situations, the parking location associated with the meter 10 is a public parking space administered by a municipal government, and the cash collection box 14 and the meter unit 16 are typically serviced by independent entities. For example, the meter unit 16 can be removed and replaced, e.g., due to upgrades, defective equipment and the like, by a provider that is contracted by the municipality to keep the parking meters 10 functioning properly. On the other hand, removal of the cash collection box 14 and emptying the currency within it are typically performed by a municipal employee. The removal and replacement of the cash collection box 14 independently of the meter unit 16 can make monitoring of both the cash collection box 14 and the removable meter unit 16 difficult.

Some embodiments of the tag units 18 and the removable meter units 16, when used with the systems and methods discussed below, can enable robust and accurate monitoring of currency collected at a specific location even if meter unit 16 removal and cash collection box 14 removal and emptying operations are independently performed. Other embodiments can enable automated updating of configuration information such as operating parameters when the removable meter unit is replaced and/or when configuration information for the specific location are updated. For example, upon replacement of an old meter unit in a meter housing, a new meter unit can automatically receive tag identification information from a tag of the meter housing and can contact a data manager to report its new location (i.e., its associated tag ID) and to receive configuration information that includes operating parameters. Similarly, removal and/or emptying of a meter cash box can automatically initiate contact from the meter unit to a data manager to report its tag ID and the cash box

activity, as well as receive configuration information. This feature is described further below. Some embodiments of the tag units **18** and the removable meter units **16** can be configured to receive configuration information such as operating parameters on demand from the data manager. The operating parameters can include any settings that effect the operation of the removable meter unit, including data such as a parking rate, a geographic location, parking rules for operation, an amount of currency in a cash box, and times when parking rates or rules apply, and the like.

In FIG. 1A and FIG. 1B, the location housing **12** is configured to permanently receive the tag **18**. The location housing **12** being configured to permanently receive the tag **18** means that the tag is affixed to the location housing such that the tag cannot be removed without leaving clear physical evidence of its removal from the location housing **12**, and/or such that removal makes the tag **18** inoperable. The tag **18** can be permanently affixed with an adhesive glue, double sided tape, single sided tape, soldering, and similar techniques that will be known to those skilled in the art.

The embodiment of the location housing **12** in FIGS. 1A and 1B is a clam-shell type of housing that is affixed to the pole **20** and is configured to mate with a removable meter unit **18**. In other embodiments, however, the location housing **12** can be a cabinet or other enclosed space that is configured to mate with one or more removable meter units, where the removable meter units are configured to be mated in compartments of the cabinet, and each of the compartments is associated with a physical location that is not necessarily at the same location as the cabinet or the compartment. In other embodiments, the location housing can be another type of receptacle fixedly placed and associated with a physical location.

Referring to FIG. 2A, functional block diagrams of examples of an exemplary removable meter unit **16-1** and a tag **18-3** are shown. The meter unit **16-1** includes a user interface **26-1** through which payment can be received. The meter unit **16-1** also includes electronic components including a processor module **28-1** and a short range interface **30** by means of which the meter unit communicates with the tag **18-3**. The tag **18-3** has a short range interface **32**, an ID module **34**, and a memory module **36** for storing information regarding configuration information including a payment collection history and/or operating parameters and meter settings. The meter unit **16-1** is linked to the tag **18-3** by a communications link **37**. In the case where the tag **18-3** is a wired tag **18-1**, the link **37** comprises a wire connecting the two, such as the wire **22** illustrated in FIG. 1A. In the case where the tag **18-3** is a wireless tag **18-2**, the link **37** can comprise a radio link or an optical link. In the case of a wireless tag **18-2**, the short range interfaces **30** and **32** between the meter unit and tag, respectively, can comprise RFID devices, Bluetooth devices, WiFi devices, IR devices, smart card devices, and the like.

The processor module **28-1** includes one or more processors such as application specific integrated circuits (ASICs), digital signal processors (DSPs), digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), processors, controllers, micro-controllers, microprocessors, other electronic units designed to perform the functions described herein, and/or a combination thereof. The processor module **28-1** also includes one or more storage mediums. A storage medium can include one or more memories for storing data, including read only memory (ROM), random access memory (RAM), magnetic RAM, core memory, magnetic disk storage medi-

ums, optical storage mediums, flash memory devices and/or other machine readable mediums for storing information.

The user interface **26-1** provides a means for a user to interact with the meter unit **16-1** and can include, for example, a display and keypad. The user interface **26-1** can provide a payment interface including a currency receiver for receiving coins and or bills in payment for using the parking location. The processor module **28-1** obtains payment information from the payment interface that provides transaction information regarding the amount of a payment received at the payment interface **26-1**. The processor module **28-1** communicates the transaction information, via the link **37**, to the short range interface **32** of the tag **18-3**. The short range interface **32** then updates the memory module **36** based on the received transaction information. The memory module **36** can add the amount of currency indicated to have been received by the transaction information to the stored amount. In addition, the memory module **36** can also receive and store transaction-time information including the date and time of day that the payment was received. In this way, when coins or bills are inserted into the meter unit **16-1** and are collected in the cash collection box **14**, the value of the coins and/or bills is determined by the meter unit **16-1** and the value stored in the memory module **36** of the tag **18-3** is appropriately updated. Thus, the tag **18-3** records the value of cash collected in the cash collection box **14** and stores the value in the memory module **36**. The memory module **36** can also store configuration information indicative of other operating parameters such as parking rate, geographic location, parking rules, an amount of currency in a cash box, and times when different parking rates or rules apply.

The ID module **34** stores a unique identifier, e.g., a tag identification or serial number, that is associated with the tag **18-3**. Preferably, the unique identifier of the tag **18-3** and the value stored in the memory module **36** are externally readable, e.g., by a suitable reader (not shown) via the interface **32**. For example, if the short range interface **32** is an RFID module, then the reader could be an RFID reader. Other types of readers that can be used depend on the embodiment, but can include IR readers, smart card readers (contact or non-contact), plug in readers, and the like. In this way, periodic downloading of the value stored in the memory module **36** can be performed with an appropriate reader to monitor the amount of cash that should be contained in the cash collection box. This downloaded cash value can then be used to detect a theft of cash, if the expected downloaded cash value does not match the collected amount of cash.

In one embodiment, the transaction information stored in the memory module **36** can be reset to zero when the cash collection box **14** is emptied or replaced. As noted above, the cash collection box **14** and meter unit **16** may be independently serviced. That is, they can be independently removed and replaced from the meter **10**. In one aspect of this embodiment, the removable meter unit **16** automatically detects when the cash collection box **14** is removed. This can be accomplished using a sensor such as a motion sensor, an IR sensor, a magnetic field sensor, or the like.

In the case of a wireless tag such as illustrated in FIG. 2A, reset to zero occurs when the removable meter unit **16-1** detects that the cash collection box **14** is removed, in which case the short range interface **30** of the removable meter unit **16-1** communicates a signal to the short range interface **32** of the tag **18-3**. In response to the signal indicating removal of the cash collection box **14**, the short range interface **32** of the tag **18-3** resets the payment collection history stored in the memory module **36** to indicate no collection history (i.e., reset to zero) and, preferably, stores the total amount of cur-

rency collected since the last cash collection box removal in the memory 36. In another aspect of this embodiment, the tag 18-3 is configured to detect the removal of the cash storage box 14 and autonomously reset the payment history and store the total amount of currency collected into the memory 36.

In another embodiment, when the cash collection box 14 is removed, an electrical circuit between the cash collection box 14 and the tag 18-3 is broken, thereby allowing the tag 18-3 to detect the removal of the cash collection box 14. In yet another embodiment, the person removing the cash collection box is required to perform an action that provides an external signal, e.g., insert a key, a magnetic stripe card, token, or smart card into the removable meter unit, thereby providing a signal that alerts the removable meter unit that the cash collection box is being removed.

Referring to FIG. 2B, functional block diagrams of other embodiments of a meter unit 16-2 and a tag 18-4 are shown. In the embodiments shown in FIG. 2B, the meter unit 16-2 includes a user interface 26-2, a processor module 28-2, the short range interface 30, and a network transceiver 31. The short range interface 30 can be the same as that in the removable meter unit 16-1 of FIG. 2A. That is, the short range interface 30 of FIG. 2B is the means by which the meter unit 16-2 communicates with the tag 18-4. The network transceiver 31 can be configured to communicate to and from wired or wireless networks. Wired networks include LANs, WANs, MANs, the Internet, intranets, and the like. Wireless networks include cellular telephone networks, WiFi networks, WiMax networks, and the like. Cellular telephone networks can be any of various technologies such as CDMA, GSM, TDMA, or the like.

The user interface 26-2 includes similar components as the user interface 26-1 of the removable meter unit 16-1 shown in FIG. 2A. In addition, the user interface 26-2 preferably includes a credit/debit card reader. The credit/debit card reader allows for the use of magnetic stripe cards and/or smart cards, tokens, and the like to be used for payment of the parking fees instead of, or in addition to, currency payments such as coins and or bills. The credit card transaction information and authorization is communicated via the network transceiver 31 to a remote transaction authorization facility, per conventional practice known to those skilled in the art.

The processor module 28-2 of the removable meter unit 16-2 shown in FIG. 2B is similar to the processor module 28-1 of the removable meter unit 16-1, but is coupled to the network transceiver 31 in order to communicate payment information to a remote data manager. The data manager is not illustrated in FIG. 2B; details of the data manager and the data communicated with the data manager are discussed further below.

Because the removable meter unit 16-2 of FIG. 2B is capable of communicating payment information to the remote data manager via the network transceiver 31, the tag 18-4 does not include a memory module 36 as in the tag 18-3 shown in FIG. 2A. When currency and/or a credit/debit card payment are received at the removable meter unit 16-2, the payment information is communicated to the remote data manager. In order for the remote data manager to be able to know at which location the payment is being received, the tag ID information stored in the ID module 34 is communicated to the remote data manager. That is, rather than store configuration information, including transaction information such as payment history, with the memory module of the tag, the FIG. 2B embodiment maintains such information at the data manager. Details of methods used to communicate between the data manager and the removable meter unit are discussed below in connection with FIG. 3.

When the removable meter unit 16-2 of FIG. 2B is first installed in the location housing 12 that contains the tag 18-4, the short range interface 30 of the removable meter unit 16-2 communicates with the short range interface 32 of the tag 18-4 and reads/receives the tag ID that is stored in the ID module 34. The tag ID and a removable meter unit ID are then communicated via the network transceiver 31 to the remote data manager. The remote data manager is coupled to a database containing unique physical locations and the tag IDs that are associated with the unique locations. The remote data manager then associates the ID of the removable meter unit 16-2 with the tag ID and with the unique physical location. In addition, any previous payment collection history that was associated with the tag ID and unique physical location is associated with the newly installed removable meter unit 16-2 and disassociated with the previous removable meter unit ID.

In addition to associating the payment collection history upon installation of a new removable meter unit, the remote data manager can also associate other configuration information such as operating parameters affecting the configuration of the meter. These operating parameters can include parking rate, geographic location, parking rules, amount of currency in a cash box, and times when different parking rates or rules apply. The operating parameters can be transmitted by the remote data manager to the removable meter unit thereby automatically updating the operating parameters of the removable meter unit. In addition to transmitting operating parameters upon installation of a new removable meter unit, a remote data manager can update the operating parameters automatically when they change.

In addition to communicating payment collection information transaction history to the data manager, the removable meter unit 16-2 can communicate an indication of removal of the cash collection box 14 to the remote data manager. In response to receiving the cash collection box removal indication, the remote data manager can reset the payment collection history in the database and record the amount of cash that was collected up to the removal event. In this way, the remote data manager can keep track of how much currency should have been collected and returned by the individual removing the cash collection box 14.

In one embodiment, the tag 18-4 includes a memory module 36 and the payment collection information can be stored in the memory module 36 to provide redundancy protection. In this way, if the network transceiver fails, the memory module 36 can store the payment collection history information. The redundant payment collection history information can be communicated to the data manager at a later date when the network transceiver 31 is replaced/repared. In addition, the memory module 36 could store other configuration information such as operating parameters, including meter settings. In this way, a new removable meter unit could retrieve the configuration information from the tag 18-4 upon installation.

Referring to FIG. 3, a parking meter system is designated generally by reference numeral 40. The system 40 utilizes a number of the parking meters 10. The parking meters 10 can be, for example, either of the parking meters 10-1 or 10-2 shown in FIGS. 1A and 1B, that include a removable meter unit 16-2 with the network transceiver 31. The parking meters 10 are operationally arranged into groups, with each group having a local data manager 42. That is, each group of parking meters 10 will report data to its associated local data manager 42 and will thereby form a local group 60. In one embodiment, there are about 30 parking meters in each local group 60. Not all the parking meters 10 are shown in the local groups 60 illustrated in FIG. 3.

11

Each of the local data managers **42** communicates with a central data manager **52**. In the system **40** of FIG. 3, this is effected by means of a cellular telephone network, with each local data manager **42** and the central data manager **52** being connected to a base station **54** of the cellular telephone network. Data links are thereby established between the local data managers **42** and the central data manager **52**. Although only three local groups **60** are shown, there can be more or fewer local groups **60**.

Each local data manager **42** has a network data modem **44**, a control device **46**, a memory **48** and a radio transceiver **50** with an antenna **38**. As indicated above, each local data manager **42** communicates with the parking meters **10** in its local group **60** via its transceiver **50** and the network transceiver **31** of the parking meter **10**. The local data managers **42** may do so directly, or indirectly via another parking meter **10** as indicated with parking meters **10-3** and **10-4**.

The memory **48** can include one or more memories for storing data, including read only memory (ROM), random access memory (RAM), magnetic RAM, core memory, magnetic disk storage mediums, optical storage mediums, flash memory devices, and/or other machine readable media for storing information. The memory **48** stores the configuration information including payment collection history information and/or operating parameters for the parking meters **10** in the local group **60**. The payment collection history information stored in the memory **48** is communicated to the central data manager **52** via the modem **44**, the base station **54** and any intervening networks such as, for example, the Internet.

The control device **46** comprises one or more processors coupled to the memory **48** and configured to control the functions associated with the radio transceiver **50** and the modem **44**. The processor **50** can include one or more of application specific integrated circuits (ASICs), digital signal processors (DSPs), digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), processors, controllers, micro-controllers, microprocessors, other electronic units designed to perform the functions described herein, and/or a combination thereof.

Alternatively to communicating with a local data manager **42**, other embodiments can provide the parking meter **10** with a network interface **31** that communicates with the central data manager **52**. In these embodiments, the network interface **31** can comprise a cellular telephone transceiver, a MAN transceiver, a satellite transceiver, or other type of transceiver that communicates over a network to the central data manager **52**.

The central data manager **52** has a controller **56** with a modem and a database store **58**. It also has a communication module for communicating with financial institutions (not shown) to obtain authorization for credit or debit card payments and payment. The modem of the central data manager **52** can be any modem configured to communicate over a network such as the Internet. The data store **58** includes a database that stores tag ID's and associates the tag IDs with the unique physical locations and the removable meter unit IDs in order to store the operating parameters including the payment collection histories and configuration information as discussed above.

To accommodate most system configurations, the transceivers **31** of the removable meter units **16-2** and the transceivers **50** of the local data managers **42** will have a power rating of about 1 mW and will have a range of about 80 meters. Thus, each local group **60** can extend over an area having a radius of about 80 meters.

12

In operation, if a person wishing to park at a parking meter wants to pay by means of a credit card, the relevant information is read by a card reader and transmitted to the central data manager **52** via the relevant local data manager **42**. The central data manager **52** obtains authorization and communicates this back to the appropriate parking meter **10** via the relevant local data manager **42**. Further, status reports, fault reporting and/or configuration and software updates, may be communicated between the parking meters **10**, the local data manager **42** and/or the central data manager **52**.

In one embodiment where the parking meter **10-3** communicates with one or more other intermediate parking meters **10-4**, and the intermediate parking meter **10-4** communicates with the local data manager **42**, the parking meters **10-3** and **10-4** communicate using a mesh network protocol. Those skilled in the art will know that mesh network protocols can be provided by several conventional communication protocols, including Bluetooth, WiFi, and 802-15 (commonly referred to as WPAN for Wireless Personal Area Network, or ZigBee).

Referring to FIG. 4, an example of a local group **60-1** of parking meters **10** that can be monitored by the parking meter system **40** of FIG. 3 is shown. The local group **60-1** includes eight parking meters **10**, but other numbers of parking meters could be included in the local group **60-1**. Each parking meter **10** is fixedly located at and associated with a parking spot **70**. The parking spots **70** are angled parking spots that could be located in a parking lot or on a street, for example.

The parking meters **10** each include a removable meter unit **16**, such as the removable meter unit **16-2** illustrated in FIG. 2B, that includes a network transceiver **31**. The eight parking meters **10** communicate, via the network transceiver **31** with the antenna **38** and the radio transceiver **50** of the local data manager **42**. The parking meters **10** can communicate directly with the local data manager **42**, as illustrated by connections **72**, or can communicate indirectly (e.g., using a mesh network) via one of the other parking meters **10**, as illustrated by the connection **74** between parking meters **10-3** and **10-4**. As discussed above, the removable meter units communicate information to the local data manager **42**, the information including tag IDs, removable meter unit IDs, payment collection information including currency received and credit/debit card information. The removable meter units can also receive configuration information such as operating parameters from the local data manager **42** upon installation or when the operating parameters are updated.

In the embodiment shown in FIG. 4, the local data manager **42** uses the modem **44** to communicate with the central data manager **52** via the Internet **80**. It should be understood that the "modem" refers to any device that provides a communication interface between the local data manager and the network. The information communicated to the central data manager **52** includes tag IDs, removable meter unit IDs, and payment collection information including currency received and credit/debit card information. The local data manager **42** can receive configuration information such as operating parameters from the central manager **52** and communicate these to the removable meter units **16**.

Referring to FIG. 5, another example of a local group **60-2** of parking meters **10** that can be monitored by the parking meter system **40** of FIG. 3 is shown. The local group **60-2** includes eight parking meters **10**, but other numbers of parking meters **10** could be included in the local group **60-2**. Each parking meter **10** is fixedly located at and associated with a parking spot **70** (only four of the eight parking spots **70** are shown). The parking spots **70** are parallel parking spots that can be located on a street, for example.

The parking meters **10** each include a removable meter unit **16**, such as the removable meter unit **16-2** illustrated in FIG. **2B**, that includes a network transceiver **31**. The eight parking meters **10** communicate, via the network transceiver **31** with the antenna **38** and the radio transceiver **50** of the local data manager **42**. The parking meters **10** can communicate directly with the local data manager **42**, as illustrated by connections **72**, or indirectly (e.g., using a mesh network) via one of the other parking meters **10**, as illustrated by connection **74** between parking meters **10-3** and **10-4**. As discussed above, the removable meter units communicate information to the local data manager **42**, the information including tag IDs, removable meter unit IDs, payment collection information including currency received and credit/debit card information. The removable meter units **16** can also receive configuration information such as operating parameters from the local data manager **42** upon installation or when the operating parameters are updated.

Referring to FIG. **6**, a flowchart of an embodiment of a process **600** for operating parking meters **10** such as the parking meters **10-1** and **10-2** of FIGS. **1A** and/or **1B** in the system **40** of FIG. **3** is shown. The process **600** includes operations performed by one or more of the local data manager **42** and the central data manager **52**. For the sake of clarity, the process **600** is described as being performed by the local data manager **42**, but it could also be performed at least in part by the central data manager **52**.

The process **600** starts at block **602**, where the radio transceiver **50** receives a tag ID that is associated in a data manager database with a unique physical location (e.g., one of the parking spots **70**) at which a removable meter unit **16** (e.g., the removable meter unit **16-1** or **16-2** of FIG. **1A** or **1B**, respectively) is placed. The tag ID received at block **602** can be received directly from the removable meter unit **16** that is placed at the unique physical location or, alternatively, can be received from an intermediate removable meter unit **16** and/or an intermediate data manager (e.g., a local data manager **42**) and/or the central data manager **52**.

As discussed above, the tag ID can be received at block **602** when a removable meter unit **16** is installed into a location housing **12** that is fixedly located and associated with the unique location.

After the tag ID is received at block **602**, processing continues at block **604**, where the control device **46** of the local data manager **42** determines configuration information associated with the tag ID and the unique physical location. The configuration information can include a transaction history and/or operating parameters associated with the tag ID and the unique physical location. The configuration information can be stored in the memory **48** of the local data manager **42** or in the data store **58** of the central data manager **52**. The configuration information is stored cross-referenced with the associated tag IDs, which are cross-referenced to the unique physical locations. In one embodiment, the stored location information comprises a hierarchical structure such as, for example, a parking spot number, on a particular street, in a predetermined zone of a given city. In another embodiment, the location information comprises GPS location information including latitude and longitude coordinates.

Upon determining the associated configuration information, the process **600** continues at block **606**, where the control device **46** associates the determined configuration information with the removable meter unit **16**. This association can be accomplished using a removable meter unit ID that identifies the removable meter unit that is located at the unique location. In one embodiment, the removable meter unit ID is received along with the tag identification at the block **602**.

The transaction information of payment collection history that is associated with the removable meter unit at block **606** can be an existing payment collection history that was previously associated with another removable meter unit **16**. Since the location housing **12** permanently receives the tag **18**, the unique physical location remains associated with the tag ID and only the removable meter unit ID association changes. Thus, the payment collection history of the unique location is associated with the new removable meter unit ID and the payment collection history can be updated.

In embodiments where the configuration information includes configuration-related operating parameters (e.g., a parking rate, geographic location, parking rules, amount of currency in a cash box, and times when parking rates or rules apply), the process **600** continues at block **607** where the radio transceiver **50** automatically transmits information indicative of the configuration-related operating parameters to the removable meter unit **16**. Such transmission can be initiated upon replacement of the meter unit or at predetermined times or in response to an event, or by a combination of all. That is, block **607** can be performed when the removable meter unit **16** is first installed and/or whenever the configuration-related operating parameters are changed. In this way, the removable meter unit **16** is automatically configured.

Upon associating the removable meter unit ID with the transaction information of payment collection history at block **606**, and in some embodiments transmitting the operating parameters at the block **607**, the process **600** continues at block **608** where the local data manager **42** monitors the local group **60** to receive, via the radio transceiver **50**, a report of a value of currency received at the removable meter unit **16**. The report of the value of currency at each meter unit **16** received at block **608** also includes the associated tag ID. Using the tag ID and the cross-reference database information stored in the memory **48**, the control device **46** can determine that the received report of the value of currency received is associated with the unique physical location where the tag **18** and the removable meter unit **16** are located.

Upon receiving the report of the value of currency received, the process **600** continues operation to block **610**, where the control device **46** associates the value of the received currency with the payment collection history and transaction information associated with the physical location and the tag ID. The association operation at block **610** can include incrementing a total value received register to reflect the newly received value and storing the updated total value. Other information that can be stored can include the date and time of day that the payment was received. Such time of day and date information can be used to modify pricing based on different demand levels measured at different times of day and/or year.

The local data manager **610** continues to perform the functions at the blocks **602-610** until the cash collection box **14** is removed from the parking meter **10**. At block **612**, the radio transceiver **50** receives a report indicating the removal of the cash collection box **14** containing currency at the removable meter unit **16**. The report received at block **612** indicates the tag ID that is associated with the unique physical location where the cash collection box **14** was removed.

Upon receiving the indication that the cash collection box **14** was removed at block **612**, the process **600** continues to block **614**, where the control device **612** determines, based on the payment collection history associated with the tag ID and stored in the memory **48**, the amount of currency that should be contained in the cash collection box at the time of removal. This amount of currency can be used to check collection operations. For example, the expected amount can be used to determine if the person collecting the currency returns an

amount that is approximately as expected and can therefore assist in preventing or detecting theft. Additionally, the control device 46 can zero-out or reset the payment collection history transaction information at the block 614.

The blocks 602 through 614 of the process 600 continue to be performed by the various modules of the local data manager 42 as needed. As discussed above, the process 600 can also be performed wholly or in part by the central data manager 52. It should be noted that one or more of the blocks of the process 600 can be rearranged, combined, or omitted.

The systems and methods discussed above involved the use of parking meters located and associated with specific parking spot locations. It should be noted that the above methods and systems are applicable to other scenarios where a measurable quantity of product or an occupied space or an amount of measurable time that a product is being consumed is associated with a meter at a unique physical location. Such scenarios may include, for example, consumption of a product at a customer station, or consumption of a resource at a production location, or waiting time at a specific location, and the like.

Specific details are given in the above description to provide a thorough understanding of the embodiments. However, it is understood that the embodiments may be practiced without these specific details. For example, circuits may be shown in block diagrams in order not to obscure the embodiments in unnecessary detail. In other instances, well-known circuits, processes, algorithms, structures, and techniques may be shown without unnecessary detail in order to avoid obscuring the embodiments.

Implementation of the techniques, blocks, steps and means described above may be done in various ways. For example, these techniques, blocks, steps and means may be implemented in hardware, software, or a combination thereof. For a hardware implementation, the processing units may be implemented within one or more application specific integrated circuits (ASICs), digital signal processors (DSPs), digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), processors, controllers, micro-controllers, microprocessors, other electronic units designed to perform the functions described above, and/or a combination thereof.

Also, it is noted that the embodiments may be described as a process which is depicted as a flowchart, a flow diagram, a data flow diagram, a structure diagram, or a block diagram. Although a flowchart may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be re-arranged. A process is terminated when its operations are completed, but could have additional steps not included in the figure. A process may correspond to a method, a function, a procedure, a subroutine, a subprogram, and the like. When a process corresponds to a function, its termination corresponds to a return of the function to the calling function or the main function.

Furthermore, embodiments may be implemented by hardware, software, scripting languages, firmware, middleware, microcode, hardware description languages, and/or any combination thereof. When implemented in software, firmware, middleware, scripting language, and/or microcode, the program code or code segments to perform the necessary tasks may be stored in a machine readable medium such as a storage medium. A code segment or machine-executable instruction may represent a procedure, a function, a subprogram, a program, a routine, a subroutine, a module, a software package, a script, a class, or any combination of instructions, data structures, and/or program statements. A code segment may

be coupled to another code segment or a hardware circuit by passing and/or receiving information, data, arguments, parameters, and/or memory contents. Information, arguments, parameters, data, and the like may be passed, forwarded, or transmitted via any suitable means including memory sharing, message passing, token passing, network transmission, and so forth.

For a firmware and/or software implementation, the methodologies may be implemented with modules (e.g., procedures, functions, and so on) that perform the functions described herein. Any machine-readable medium tangibly embodying instructions may be used in implementing the methodologies described herein. For example, software codes may be stored in a memory. Memory may be implemented within the processor or external to the processor. As used herein the term "memory" refers to any type of long term, short term, volatile, nonvolatile, or other storage medium and is not to be limited to any particular type of memory or number of memories, or type of media upon which memory is stored.

Moreover, as disclosed herein, the term "storage medium" may represent one or more memories for storing data, including read only memory (ROM), random access memory (RAM), magnetic RAM, core memory, magnetic disk storage mediums, optical storage mediums, flash memory devices and/or other machine readable mediums for storing information.

While the principles of the disclosure have been described above in connection with specific apparatuses and methods, it is to be clearly understood that this description is made only by way of example and not as limitation on the scope of the disclosure.

We claim:

1. A meter apparatus comprising:

a tag that stores unique tag identification information and is configured to be permanently affixed to a location housing at a physical location; and

a removable meter unit configured to mate with the location housing and receive the tag identification information from the tag and report the tag identification information and an identifier of the removable meter unit to a data manager that is configured to determine configuration information for the identified removable meter unit based on the physical location corresponding to the reported tag identification information;

wherein the meter apparatus comprises a parking meter and the removable meter unit is configured to receive the configuration information from the data manager and store the configuration information, including parking rate and operating rules.

2. The meter apparatus of claim 1, wherein the tag comprises a memory module configured to store information indicative of a payment collection history, and the tag is further configured to receive information indicative of a payment received at the removable meter unit and update the information indicative of the payment collection history to reflect the payment received at the removable meter unit.

3. The meter apparatus of claim 2, wherein the tag is further configured to:

receive information indicative of removal of a cash collection box containing currency received at the removable meter unit; and

in response to receiving the information indicative of the removal of the cash collection box, store in the memory module information indicating the amount of currency collected at the removable meter unit based on the stored payment collection history.

17

4. The meter apparatus of claim 3, wherein the tau is further configured to reset the payment collection history stored in the memory module in response to receiving the information indicative of the removal of the cash collection box.

5. The meter apparatus of claim 1, wherein the removable meter unit is further configured to identify a value of currency received at the meter, and report the value of the received currency and the tag identification to the data manager such that the data manager associates the value of the received currency with a payment collection history of the physical location and the tag identification.

6. The meter apparatus of claim 5, wherein the removable meter unit is further configured to detect removal of the currency received at the meter, and report an indication of the removal of the currency and the tag identification to the data manager such that the data manager determines, based on the associated payment collection history, the amount of the currency removed.

7. The meter apparatus of claim 1, wherein, subsequent to the data manager associating configuration information for the physical location with the removable meter unit and the tag identification, the removable meter unit receives information indicative of operating parameters from the data manager.

8. The meter apparatus of claim 7, wherein the received operating parameter information is indicative of at least one

18

of a parking rate, a geographic location, parking rules, an amount of currency in a cash box, and times when parking rates or rules apply.

9. The meter apparatus of claim 1, wherein the removable meter unit reports the tag identification to the data manager via a wireless communication channel.

10. The meter apparatus of claim 1, wherein the removable meter unit receives the tag identification wirelessly.

11. The meter apparatus of claim 1, wherein the removable meter unit is configured to receive the tag identification and report the to identification to the data manager upon being mated to the location housing.

12. The meter apparatus of claim 1, wherein the data manager maintains the identifier of the removable meter unit, the reported tag information, unique physical location, and configuration information in a database external to the meter apparatus.

13. The meter apparatus of claim 1, wherein the removable meter unit is further configured to store transaction information into the tag for reporting to the data manager, the transaction information comprising payment collection history generated by the removable meter unit during operation.

14. The meter apparatus meter apparatus of claim 1, wherein the removable meter unit is further configured to report the tag identification information and identifier to the data manager in response to mating with the location housing.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,002,723 B2
APPLICATION NO. : 12/355740
DATED : April 7, 2015
INVENTOR(S) : King et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Claims

Column 17, line 1, Claim 4, please delete “tau” and replace with --tag--

Column 18, line 11, Claim 11, please delete “report the to” and replace with --report the tag--

Column 18, line 23, Claim 14, please delete “meter apparatus meter apparatus” and replace with --meter apparatus--

Signed and Sealed this
Twenty-fourth Day of November, 2015



Michelle K. Lee
Director of the United States Patent and Trademark Office